

# HIGH SPEED BAND SEALER

## Heavy, Elite, Eco

### HIGH SPEED BAND SEALER

#### Easy to use

Intuitive design, touchscreen interface, and easy access to sealing section.

#### Seal Integrity

Consistent, strong hermetic seals that keep your product pure, fresh, and secure.

#### Plug and Play

Modular design provides easy installation, expandability and quick turnaround.

#### Real Packing Value

Standard and custom Solutions that fit your unique budget And requirements.



### MACHINE SERIES

#### Heavy ( H Series )



#### Elite ( E Series )



#### Eco ( Eco Series )



### TECHNICAL INFORMATION

#### Case Erectors

Reliability	Heavy (H Series)	Elite (E Series)	Eco (Eco Series)
Electrical	220-230V, 50/60Hz	220-230V, 50/60Hz	220-230V, 50/60Hz
Motor	90W "Oriental Motor"	90W "Oriental Motor"	90W "Oriental Motor"
Sealer Duty	Continuous	Continuous	Continuous
Infeed Direction	Right and Left	Right and Left	Right and Left
Sealing Band	Teflon	Teflon	Teflon
Sealing Orientation	Vertical	Vertical and Horizontal	Vertical and Horizontal
Variable Speed	up to 15 m/min.	up to 25 m/min.	up to 25 m/min.
Sealing Capacity	5-20 kg.	1-5 kg.	0.1-1 kg.
Sealing Width	12-20 mm.	6-20 mm.	6-20 mm.
Sealing Depth	80 mm.	80 mm.	80 mm.
Temperature Range	200-280 °C	200-280 °C	200-280 °C
Food Grade Conveyor	PU Belt, Stainless Steel	PU Belt, Stainless Steel	PU Belt, Stainless Steel
Frame Construction	Aluminum	Aluminum	Aluminum
Controller	PLC OMRON, HMI 6"- Colour	PLC OMRON, HMI 6"- Colour	Microcontroller, HMI 6"- Colour